



---

# ADX-49M

## 4.4-5.0 GHz Omni directional MIL Grade Antenna 9.5 dBi

### Recommend for Japanese band 5G N79

---

The ADX-49M is a very compact yet high performance Heavy duty MIL grade omnidirectional WiFi antenna designed for the 4.4 - 5.0 GHz ISM and UNII band. It is ideally suited for multipoint and mobile applications where high gain and wide coverage is desired.

The ADX-49M construction features a fiberglass radome for durability and aesthetics. Included with the antenna, the mounting system features a heavy-duty steel bracket and U-Bolt for superior strength.

**Recommend for Japanese band 5G N79**



Electrical and Mechanical Specifications	
Frequency	4400-5000 MHz
Gain	9.5 dBi
Horizontal Beam Width	360 degrees
Vertical Beam Width	16 degrees
Connector	N Female
VSWR	< 1.5:1 avg.
Impedance	50 Ohm
Max. Input Power	150 Watts
Weight	0.44 lbs. (0.2 kg)
Dimensions	1.0" Dia. x 17.5" Length
Mounting	2" (50.8 mm) dia. mast max.
Radome Material	Gray Fiberglass
Operating Temperature	-40° C to to 85° C(-40° F to 185° F)

RF Antenna Gain Patterns

