

VRX-24LX

Audio/Video Receiver 2.4 GHz

This is the extremely sensitive and definitely the best small 2.4 GHz Audio/ Video receiver on the market. Fully synthesized this receiver has an SMA connector for different type of antennas 2.4 GHz. This receiver comes in options with 2, 4 or 8 selectable channels. This receiver works for any TV system. A special AFT and AGC features are incorporated with this receiver, it is recommended to use it with smallest Video transmitters DX series.



Dimensions: 2.8 " X 1.5 " X 0.75 ".

Technical Specifications	
Operating Frequencies:	2300 MHz- 2500 MHz
Channel:	#2, 4, 8
DC Voltage:	9 V- 12 V
RF power:	N/A
Minimum required voltage:	9 V
Battery power:	12 V/ 360 mA
Video distortion:	3%
Sensitivity:	-98 dBm
Video Format:	PAL, NTSC
Current Consumption:	360 mA / 9 V
Antenna:	Recommended high gain, omni directional ant.
Antenna Connector:	SMA
Impedance:	50 ohms
Video output Connector:	RCA F
Video Impedance:	75 ohms
Temperature Range:	-25 +65* C
Dimensions:	2.8" X 1.5" X 0.75"
Weight:	50 grams
Demodulation:	WFM