



ZHM 20-1000/100 MIL GRADE HIGH POWER AMPLIFIER 20 MHz TO 1 GHz 100 W



Export restricted item

This amplifier operates from 20 MHz to 1000 MHz, ideal for broadband military platforms as well as commercial applications because it is robust and offers high power over a multi-octave bandwidth. It was designed for broad band jamming and communication systems platforms and its bandwidth can be extended to 1200 MHz+ with similar performance. It is packaged in a modular housing that is approximately 3.4" (width) by 6.4" (long) by 1.0" (height). This amplifier has a typical P3dB of 100 watts at room temperature. Noise figure at room temperature is 10.0 dB typical. It offers a typical gain of 58 dB with a typical gain flatness of ± 2.0 dB. The power and gain flatness across the band is extremely flat for the bandwidth. Input VSWR is 2.0:1 maximum. Class AB quiescent current is ~ 2.0 amps typical employing a +28 Vdc supply. This PA operates from a +28 Vdc input voltage. Typical harmonic values can be found on the next page of this data sheet. It operates from -40C to +85C base plate

- Gallium Nitride Broadband Power Amplifier
- Operation from 20 MHz to 1000 MHz min
- Small Signal Gain 58 dB typical
- 40 to 60% Typical Power Added Efficiency
- 100 Watts P3dB typical

Freq (MHz)	Small Signal Gain (dB)	P3dB (dBm)	Current @ P3dB from a 28 Vdc Supply (Amps)	2nd Harmonic @ P1dB (dBc)	3rd Harmonic @ P1dB (dBc)	Power Added Efficiency (%)
20	56.1	49.9	7.5	-13.0	-13.0	46.5
50	56.5	50.1	7.5	-13.0	-25.0	48.7
100	58.3	51.1	8.0	-19.5	-18.0	57.5
200	59.0	51.1	7.5	-20.0	-21.0	61.3
300	59.0	50.6	7.0	-17.0	-24.0	58.5
400	59.5	50.2	6.7	-23.0	-25.0	55.9
500	58.0	49.6	6.9	-22.0	-28.0	47.2
600	56.5	48.8	6.7	-14.0	-34.0	40.4
700	57.3	49.8	8.0	-25.0	-41.0	42.6
800	59.0	48.6	6.8	-29.0	-42.0	38.0
900	57.4	48.7	6.4	-50.0	-47.0	41.3
1000	60.0	49.8	7.2	-40.0	-40.0	47.4