



KX-4010

AUDIO/VIDEO TRANSMITTER

FOR ALL UHF FREQUENCIES

FROM 430-920 MHz

NEW!

The world's smallest audio/video transmitter KX-4010 is a special design for all UHF frequencies from 430-927 MHz. This video transmitter is very small, it measures 1.5"x 0.8". It is easy to use. Required DC power is 9 V-12 V/ 120 mA. It is excellent audio/video transmitter for video surveillance applications or experiments.



Technical Specifications	
Operating Frequencies:	430-918 MHz
Channels:	SELECTABLE ON BOARD
DC Voltage:	9 V – 12 V
RF power:	50 mW
Minimum required voltage:	7 V
Battery power:	9 V
Video distortion:	3%
Maximum range:	500 ft
Video Format:	PAL or NTSC
Current Consumption:	128 mA
Antenna:	Built-in,
Antenna Connector:	N/A
Video Connector:	RCA or open wire
Video Impedance:	75 ohms
Video level:	1 V
Temperature Range:	-20 +75* C
Dimensions:	1.5" X 0.8 " X 0.1"
Weight:	8 grams
Modulation:	Negative AM

Note: BLACK wire Ground/ Common, WHITE wire CMOS camera input, GRAY wire CCD camera input