



LUV-1000MX VIDEO TRANSMITTER 2.4 GHz

EXCELLENT FOR COVERT
APPLICATIONS

The newest **1000 mW** audio/video transmitter for 2.4 GHz is the best smallest transmitter on the market with amazing power of 1 W. This is the world's smallest 1 W video transmitter. It requires power supply 12 V with a current consumption 360 mA! This transmitter is the best tested unit for Airplane models. LUV-1000MX has 8 on board selectable channels.



Technical Specifications	
Operating Frequencies:	2300 MHz- 2500 MHz
Channel:	8 channels
DC Voltage:	7.5-12 VDC
RF power:	1000 m W
Minimum required voltage:	7.5 V
Battery power:	9 V
Video distortion:	2%
Maximum range:	8 km from the AIR
Video Format:	PAL, NTSC
Current Consumption:	360 mA / 5 V
Antenna:	Omni Dipole recommended
Antenna Connector:	SMA
Impedance:	50 ohms
Video Connector:	RCA F or open wire
Video Impedance:	75 ohms
Video level:	1 V
Audio input:	300 mV
Temperature Range:	-40 +75* C
Dimensions:	2.5" X 1.5 " X 0.75"
Weight:	50 grams
Modulation:	WFM

WARNING:

**This unit works only with 12 V DC power.
Do not connect over 14 V DC.**