



MTR-2400 SPECIAL UHF MONITOR VIDEO RECEIVER

The 2.4 GHz audio/video receiver with LCD TFT screen module for any UHF TV transmitter is a perfect solution for any professional user and commercial application as well. This receiver covers 4 channels from 2300-2400 MHz made for special applications and receiving a picture from a smallest video transmitters DX series. Required power supply is 9 V- 12 V DC/ 350 mA. Video formats: 4:3 and 16:9.

Dimensions: 4.5. " X 3.0 " X 1.2 "



| Technical Specifications | |
|--------------------------|-------------------------------------|
| RF: | |
| Input Frequency: | 2400 MHz, 4 channels, No deemphasis |
| Sensitivity: | -95 dBm (built in preamplifier) |
| Output Impedance: | 75 Ohms. |
| VIDEO: | |
| Output Level: | 1.0 Vp-p, NTSC |
| Output mode: | WFM |
| panel control | ± 10dB. |
| Formats: | 4:3 and 16:9 |
| Output Impedance: | 75 Ohms. |
| GENERAL: | |
| DC Power Input: | +12 VDC @ 350 mA, |
| Temperature: | 0° C to +50° C. |
| Dimensions: | 1" W*3.5"H*7.5"D. |
| Weight: | 300 gr |