

## S-430/S1 LOW COST COMPLETE RACING UHF WIRELESS SYSTEM 434 MHz AM



UHF complete wireless TV system S-430/S1 is an excellent solution for car racing. It comes with a high power video transmitter 5 W, receiver M-806, dipole antenna and magnet mount antenna 3 dB gain. This system is excellent to send a broadcast quality video signal over 5 km.

<b>Technical Specifications</b>	S-430/S1 Transmitter
Operating Frequency:	433.25 MHz
Channel:	1
DC Voltage:	12 V
RF output power:	5 W / 50 ohms
Minimum required voltage:	12 V
Battery power:	12 V - 14.4 V
Frequency stability:	+-20 ppm
Video distortion:	3%
Maximum range:	15 km with directional antennas 10 dB
Video Format:	PAL, NTSC
Current Consumption:	2.5 A / 12 V
Antenna:	Omni Directional 5 dB included
Antenna Connector:	SMA/N
Impedance:	50 ohms
Video Connector:	RCA Female
Video level:	1 V
Video Impedance:	75 ohms
Audio frequency response:	N/A
Audio input:	No Audio
Audio carrier frequency:	N/A
Temperature Range:	-40 +75* C
Dimensions:	8" X 6" X 3.5"
Weight:	2 lb

Modulation:	Negative AM
<b>Technical Specifications</b>	S-430/S1 Receiver
Operating Frequency:	433.25 MHz
Number of Channels:	1
Current Consumption:	350 mA / 12 V
DC Voltage:	12 V
Sensitivity:	-80 dBm
Minimum required voltage:	12 V
Battery power:	12 V -14.4 V
Video distortion:	3%
IF frequency:	45 MHz
IF bandwidth:	6 MHz
Gain flatness:	3 dB
Noise:	1.8 dB
Image rejection:	45 dB
Antenna:	Directional 8 dB included
Antenna Connector:	SMA/N
Impedance:	50 ohms
Video Connector:	RCA Female
Video Impedance:	75 ohms
Audio output:	N/A
Video level:	1 V
Temperature Range:	-40 +75* C
Dimensions:	2" X 2" X 1"
Weight:	0.5 lb
Modulation:	Negative AM