



VRX-24LTS/M

Audio/Video Receiver 2.4 GHz

The newest Military Grade 2.4 GHz Audio/video receiver VRX-24LTS/M has excellent performances and it is the most sensitive receiver for 2.4 GHz band on the market! VRX-24LTS/M has fully tunable function in 2.2 GHz - 2.50 GHz frequency range. Video output is 75 ohms standard for any TV monitor. VRX 24LTS/M has built-in a sound and encryption demodulator as well. The power supply is 9-12V/200 mA. Antenna connector is an SMA type. The VRX-24LTS is excellent solution for mobile use. You can easy and fast scan all video/audio transmitters in 2.4 GHz band by connecting this receiver to any TV monitor.



Technical Specifications	
Operating Frequencies:	FULLY TUNABLE IN 2.2- 2.5 GHz BAND
Encryption decoder:	Yes
DC Voltage:	9 V- 12 V
RF power:	N/A
Minimum required voltage:	9 V
Battery power:	12 V/ 300 mA
Video distortion:	2%
Sensitivity:	-85 dBm
Video Format:	PAL, NTSC
Current Consumption:	200 mA / 9 V
Antenna:	Recommended high gain, omni directional ant.
Antenna Connector:	SMA
Impedance:	50 ohms
Video output Connector:	RCA F
Video Impedance:	75 ohms
Audio outputs:	RCA 300 mV
Carrier frequencies for audio channels:	6 MHz and 6.5 MHz
Temperature Range:	-20 +70* C
Dimensions:	6.0" X 4.0 " X 1.2"
Weight:	350 grams