

ZHS50-300/250
HIGH POWER AMPLIFIER FOR LTE BAND
50 MHz – 300 MHz



Designed for Testing, labs and Special purposes, transmitters, this amplifier incorporates microstrip technology and LDMOS device to enhance ruggedness and reliability.

Size (base plate): 6" x 4" x 3"

- 50 MHz-300 MHz • 48 Volts
- Input/Output 50 Ω
- Pout : 250 W min
- Standby Curent 85 mA
- Max curent 10.8 A
- Gain : 23 dB typ
- Class B

Electrical Specifications:

ELECTRICAL SPECIFICATIONS (Base Plate T. = 45 °C, 50Ω loaded, Vd = 48 V)

ELECTRICAL				
Characteristics	Min	Typ.	Max	Unit
Operating Frequency Range	46		315	MHz
Fundamental Output Power	250			W
Power Input		2	2.5	W
Power Gain (250W output)		23		d B
I Drain		9.5	11	A
Collector Efficiency (Load 50Ω)		86		%
Input VSWR		1.3:1	1.7:1	
Insertion Phase Variation (Unit to Unit)		±10		Degrees
Power Gain Variation (Unit to Unit)		±1		d B
F2 Second Harmonic	-35	-42		d B
F3 Third Harmonic		-39		d B

Copyright © 2001-2023 RF-LINKS